

 [Send to Printer Close Window](#)

Search result: 1 of 1

(WO/2004/015625) MULTI-FREQUENCY IDENTIFICATION DEVICE

Biblio. Data	Description	Claims	National Phase	Notices	Documents
--------------	-------------	--------	----------------	---------	-----------

Latest bibliographic data on file with the International Bureau

Publication Number: WO/2004/015625 **International Application No.:** PCT/IB2003/003743
Publication Date: 19.02.2004 **International Filing Date:** 08.08.2003
Chapter 2 Demand Filed: 08.03.2004

Int. Class.7: G06K 19/07

Applicants: BNC IP SWITZERLAND GMBH [CH/CH]; Saegestrasse 5, CH-9230 Flawil (CH) *(All Except US)*.
 MARTINEZ DE VELASCO, Cortina, Francisco [MX/MX]; Sierra Amatepec #213, Lomas de Chapultepec, Mexico, D.F. 11000 (MX) *(US Only)*.
 RIETZLER, Manfred [DE/DE]; Am Alsterberg #10, Marktoberdorf 87616 (DE) *(US Only)*.

Inventors: MARTINEZ DE VELASCO, Cortina, Francisco [MX/MX]; Sierra Amatepec #213, Lomas de Chapultepec, Mexico, D.F. 11000 (MX).
 RIETZLER, Manfred [DE/DE]; Am Alsterberg #10, Marktoberdorf 87616 (DE).

Agent: MIDGLEY, Jonathan, Lee; Marks & Clerk, 57-60 Lincoln's Inn Fields, London WC2A 3LS (GB).

Priority Data: 60/401,762 08.08.2002 US

Title: MULTI-FREQUENCY IDENTIFICATION DEVICE

Abstract: The present invention comprises a radio frequency identification device that utilizes multiple operating frequencies. In one embodiment of the present invention, one frequency (e.g., an ultra-high frequency such as 915 MHz, 800 MHz, 915 MHz, or microwave frequency such as 2.45 GHz) is used for data transmission, and another frequency (e.g., a low or high frequency such as 13.56 MHz) is used for field penetration. In another embodiment, one frequency is used for reading information received from the multi-frequency identification device, and another frequency is used for writing to the multi-frequency identification device. In an additional embodiment, the multi-frequency identification device utilizes one antenna for all frequencies. In another embodiment, the multi-frequency identification device utilizes two or more antennas for different frequencies, and one common memory. In other embodiments, one or two digital parts, analog parts, antennas, and memories can be used.

Designated States: AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.
 African Regional Intellectual Property Org. (ARIPO) (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW)
 Eurasian Patent Organization (EAPO) (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM)
 European Patent Office (EPO) (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE, SI, SK, TR)
 African Intellectual Property Organization (OAPI) (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Publication Language: English (EN)
Filing Language: English (EN)